



CORRUGATOR LINE FOR SALES 2.200 mm



This Machine S&S (USA) 2.200 MM/ 86", LHDPG, COMPLETE CORRUGATING LINE 1977 model

SPEEDS

Single wave average: 110 mt/min

Double wave average: 90 mt/min

Mixed average: 95 mt/min

Production capacity: 2500ton/month

Works Paper

Liner paper: min 90gr/m² max 200gr/m²

Ondula paper: min 80gr/m² max 180gr/m²

WET END

- 5 Roll stand mod. PBB , REE brakers
- 5 TORRES Splicer mod. CTS-D
- 2 Preheater mod. PRR
 - 1 Single facer S&S B flute, for glue with coolant system all cylinders are renewed – (7.113.218mt)
 - 1 Single facer C flute, - for glue with coolant system all cylinders are renewed – (7.99.4904 mt)
- Triple Preheater. PRTTR
- Double Gluer S&S glue unit mod. Touch Screen
- Double Bridge mod. PDT
- Double Brake
- Double Backer model SHORT PRESS S&s 12 Equipped with hot iron plates



DRY END

Automatic slitter scorer TCY 2001 AS2D22 Model 2500mm 12scorrer 7 knife

Cut-off Double S&S knife

Vacuum conveyor cut-off mod. VEC duplex

Automatic stacker S&S

The machine is available in a plant with highly efficient and strict maintenance schedule, can be seen at the time of production.

