



OCC LINE FOR 200 – 400 TPD



Composed by:

1. 2 Pear Lamort size II work on continuous with power motor 45 kW on stainless steel with valves with screws and reject press
2. 2 x HDC Liquid Cyclone model 14 ½ with set of valves flow 10.000 l/min per unit
3. 2 x Lamort ADS7 fractionator double stage screen 1st stage holes 3,5 mm and 2nd stage slots 0,2 mm with valves no motor included
4. 2 x Lamort Diabolo DF2 with holes 2,7 mm and power motor 45 Kw
5. Andritz low density cleaner section composed by:
 - 34 cones type 133LH34
 - 5 cones ELP940PR
 - 2 cones ELP940PR
 - 2 cones ELP940BC
6. Lamort SPN10 with slotted basket 0,2 mm and power motor 90 kW capacity 220 Tpd
7. Escher Wyss BIRD 50 double screen basket with slotted and holes baskets and power 37 kW
8. Escher Wyss BIRD 50 double screen basket with slotted and holes baskets and power 37 kW
9. Lamort CH5A slotted basket 0,25 mm and power motor 45 kW and capacity 50 Tpd
10. 2 x drum thickeners width 4.500 mm and diameter 1.525 mm with power motor

11. Complete hot dispersion unit KRIMA year 1998 composed by:

- 2 dewatering press model SD2040 with power motor 11 kW
- Shredder model 400 – 2 power 5,5 kW
- Screw press RR 550 with power 55 kW
- Plug screw 3823 with power 30 kW
- Shredder model 400 with power motor 7,7 kW
- Preheater model 10050 power motor 11 kW
- In feeder type 350 power motor 7,5 kW
- Disperger model KD710 with power motor 400 kW without adjust disc system reused by the mill
- Spare screws



12. Lamort SPN10 with slotted basket 0,2 mm and power motor 90 kW capacity 220 Tpd (accepts from fractionator)
13. Escher Wyss BIRD 50 double screen basket with slotted and holes baskets and power 37 kW (accepts from fractionator)
14. Pulp and water pumps TURO EGGER and Andritz
15. Agitators and some regulation, pipes on stainless steel and Iron

